



The simple LARGA wall-mounted light captivates with its linear design and high-quality aluminium housing, which is available in two different surfaces. Not only do they set the stage with their modern housing shape, however, but also create a pleasant lighting atmosphere with their indirect warm white light.

Special features

- Indirect light
- High colour reproduction value

Housing Material	Die-cast aluminium
Housing Color	Silver
Housing Surface	Brushed
Material of Lens	Plastic
Surface Structure of Lens	Opal
Protection Class	Protection class I/protective grounding
Rated Input	9 W
Rated Input Voltage Frequency	100-277 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	No
Motion Detector	No

Storage Temperature	-10 to 60 °C
IP Protection Class	IP 20
Life Time L70 / B50	20000 h
Switching Cycles	150000
Power Consumption	9 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	770 lm
Rated Angle of Reflection	110 Degree
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Indirect
Light direction	Rear

Length	910 mm
Width	44 mm
Height	44 mm
Base length	170 mm
Base width	44 mm
Base height	37 mm

Working Temperature	-5 to 40 °C
----------------------------	-------------