

**Special features**

- Including 0.5 m connecting cable

Housing Material	Stainless steel, Die-cast aluminium
Housing Color	Silver
Material of Lens	Glass
Protection Class	Protection class I/protective grounding
Rated Input	5.8 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Cable Primary	Yes
Primary Connection	Connection box
Primary Cable Length	0.5 m
Dimmable	No
Motion Detector	No

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	400 lm
Luminous Efficiency	69 lm/W
Rated Angle of Reflection	20 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top

Height	44 mm
Diameter	116 mm
Installation Depth	44 mm
Cut Out Diameter	105 mm
Product weight	694 g

Working Temperature	-20 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 67
Load Force max.	5 kN
Life Time L70 / B50	25000 h
Switching Cycles	100000
Power Consumption	6 kWh/1000h
Energy Efficiency Class	G