



Whether in high-bay warehouses, in large sales areas or in extensive presentation spaces - ALUDRA series pendant lamps prove highly capable as universal high-bay downlighters for use at height. Thanks to their high luminous flux, wide light emission angle and IK10 impact strength class, ALUDRA lights bring functional light to large areas safely and reliably.

Special features

- Including 3 m connecting cable
- High impact resistance
- High luminous intensity

Housing Material	Aluminium
Housing Color	Black
Protection Class	Protection class I/protective grounding
Rated Input	190 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Cable Primary	Yes
Primary Connection	With free strand / conductor ends
Primary Cable Length	3 m
Connection Cable Secondary	Yes
Secondary Cable Length	3 m
Dimmable	Yes
Control technology	DALI 1 / DT6
Motion Detector	No

IK Protection Class	IK10
Life Time L70 / B50	50000 h
Switching Cycles	25000
Power Consumption	190 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	5000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	29315 lm
Rated Angle of Reflection	120 Degree
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Height	178 mm
Diameter	405 mm

Working Temperature	-20 to 50 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 65

