


Art. no. 342233

Standing lamp Office Three Pro, Motion, 80 W, DIM,
2700-6500 K, black



Housing Material	Aluminium	Length	1240 mm
Housing Color	Black	Width	64 mm
Material of Lens	Polycarbonate - PC	Height	1950 mm
Protection Class	Protection class I/protective grounding	Base length	530 mm
Rated Input	80 W	Base width	225 mm
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz	Base height	10 mm
Power Supply Unit incl.	Yes	Product weight	11740 g
Primary Connection	Safety plug	Working Temperature	-20 to 45 °C
Primary Cable Length	2.5 m	Storage Temperature	-40 to 80 °C
Connection Type According to Standard	Typ X	IP Protection Class	IP 20
Dimmable	Yes	IK Protection Class	IK06
Control technology	Touch-Sensor	Life Time L80 / B10	50000 h
Motion Detector	Yes	Switching Cycles	100000
Kind of Motion Detector	High frequency	Power Consumption	80 kWh/1000h
Detection Distance	0-3.5 m	Energy Efficiency Class Lightsource	This product contains light sources of energy efficiency classes D and F.
Angle of Detection	85 Degree		
Light Source	LED, Light source changeable TC		
Lightcolor	Warm white/neutral white/cold white		
Colour Temperature	2700-6500 K		
Colour Consistency	3 SDCM		
Colour Rendering Index (Ra)	95		
Rated Luminous Flux	9000/9800 lm		
Luminous Efficiency	122.5 lm/W		
Rated Angle of Reflection	120 Degree		
Rated Angle of Reflection 2	50 Degree		
UGR	6		
Light Exit Surfaces	2		
Light characteristics	Direct, Indirect		
Light direction	Top, Below		