



The square JABBAH uses integrated COB LEDs in warm white, emitting its light asymmetrically at an angle of 75° onto walls in a cone of illumination - in a simple variant providing 915 lumens, as an UP AND DOWN version providing a total of 1,850 lumens. In addition, the two-sided JABBAH can be dimmed to 60 % luminous flux using a dip switch, if a more subtle light is desired.

Special features

- Modern design
- Dimmable to 60 % using DIP switch
- High luminous flux

Housing Material	Die-cast aluminium	Energy Efficiency Class	G
Housing Color	Grey		
Protection Class	Protection class I/protective grounding		
Rated Input	13 W		
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	915 lm		
Rated Angle of Reflection	75 Degree		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Length	150 mm		
Width	150 mm		
Height	150 mm		
Working Temperature	-20 to 40 °C		
Storage Temperature	-10 to 60 °C		
IP Protection Class	IP 65		
Life Time L70 / B50	30000 h		
Switching Cycles	15000		
Power Consumption	13 kWh/1000h		