

**Special features**

- Max. suspended mounting 1,600 mm
- Concrete housing
- Exchangeable lamp (E27)

<b>Housing Material</b>	Concrete
<b>Housing Color</b>	Grey
<b>Housing Surface</b>	Matt
<b>Protection Class</b>	Protection class I/protective grounding
<b>max. Power</b>	1x max. 25 W
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz
<b>Socket Description</b>	E27
<b>Socket Quantity</b>	1
<b>Connection Type</b>	Clamp
<b>Dimmable</b>	Yes
<b>Control technology</b>	Dimmable via optional light source
<b>Motion Detector</b>	No
<b>Execution</b>	Without lamp
<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Below
<b>Height</b>	188 mm
<b>Diameter</b>	188 mm
<b>Base height</b>	25 mm
<b>Base diameter</b>	120 mm
<b>Pendulum Length max.</b>	1800 mm
<b>Product weight</b>	2712 g
<b>Working Temperature</b>	-5 to 40 °C
<b>Storage Temperature</b>	-10 to 50 °C
<b>IP Protection Class</b>	IP 20