



Special features

- Low installation height

Housing Material	Stainless steel
Housing Color	Silver
Housing Surface	Brushed
Material of Lens	Glass
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant voltage
Rated Input	0.6 W
Rated Input Voltage	12 V/DC
Power Supply Unit incl.	No
Connection Cable Secondary	Yes
Secondary Connection	Open cables
Secondary Cable Length	2 m
Dimmable	No
Motion Detector	No

Product weight	97 g
Working Temperature	-5 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 20
Life Time L70 / B50	25000 h
Switching Cycles	100000
Power Consumption	1 kWh/1000h

Light Source	LED, Light source not changeable
Color Temperature	4500 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	30 lm
Luminous Efficiency	50 lm/W
Rated Angle of Reflection	60 Degree
Light Distribution	Symmetric

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Length	70 mm
Width	70 mm
Height	6.5 mm
Installation Depth	7 mm
Cut Out Diameter	56 mm