



Compact, subtle, impactful - Zilly series surface-mounted wall lights can be installed on patios, building walls or in entrances to living spaces and look exquisite in any location with their stainless steel housing and light emanating upwards and/or downwards. The dimmable light sources each with max. 35 W are in GU10 holders. They are available in variants with or without movement sensors

<b>Housing Material</b>	Stainless steel
<b>Housing Color</b>	Silver
<b>Material of Lens</b>	Glass
<b>Protection Class</b>	Protection class I/protective grounding
<b>max. Power</b>	2x max. 35 W
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz
<b>Socket Description</b>	GU10
<b>Socket Quantity</b>	2
<b>Connection Type</b>	Clamp
<b>Motion Detector</b>	Yes
<b>Kind of Motion Detector</b>	Infrared
<b>Detection Distance</b>	1-8 m
<b>Angle of Detection</b>	90 Degree
<b>Execution</b>	Without lamp
<b>Light Exit Surfaces</b>	2
<b>Light characteristics</b>	Direct, Indirect
<b>Light direction</b>	Top, Below
<b>Length</b>	220 mm
<b>Width</b>	70 mm
<b>Height</b>	108 mm
<b>Diameter</b>	60 mm
<b>Base length</b>	148 mm
<b>Base width</b>	67 mm
<b>Base height</b>	25 mm
<b>Product weight</b>	714 g
<b>Working Temperature</b>	-20 to 50 °C
<b>Storage Temperature</b>	-10 to 60 °C
<b>IP Protection Class</b>	IP 44