



Equipped with LEDs in a neutral white light colour [4,000 K], the TRIPROOF LED IP65 damp-proof light consists of a light grey polycarbonate housing and a satin-finished polycarbonate cover in one piece. It is suitable for simple ceiling, wall or suspended mounting and is available in three different lengths. Several lights can be connected in series; ideal for industrial and private use, e.g. for lighting under canopies, in cellar rooms, workshops, garages, industrial halls etc. The light has a simple electrical connection with push-in connector.

Special features

- High impact resistance
- Feed-through wiring possible

| | |
|-------------------------|---------|
| Housing Material | Plastic |
| Housing Color | White |
| Housing Surface | Matt |

| | |
|--------------------------------|--------------|
| Power Consumption | 35 kWh/1000h |
| Energy Efficiency Class | G |

| | |
|--------------------------------------|---|
| Protection Class | Protection class II/protective insulation |
| Rated Input | 35 W |
| Rated Input Voltage Frequency | 180-240 V/AC 50 / 60 Hz |
| Power Supply Unit incl. | Yes |
| Connection Type | Clamp |
| Dimmable | No |
| Motion Detector | No |

| | |
|---|----------------------------------|
| Light Source | LED, Light source not changeable |
| Color Temperature | 4000 K |
| Colour Consistency | 6 SDCM |
| Colour Rendering Index (Ra) | 80 |
| Rated Luminous Flux | 2980 lm |
| Rated Angle of Reflection | 120 Degree |
| Distribution Characteristic 120° | NDLS |

| | |
|------------------------------|--------|
| Light Exit Surfaces | 1 |
| Light characteristics | Direct |
| Light direction | Below |

| | |
|---------------|---------|
| Length | 1296 mm |
| Width | 61 mm |
| Height | 56 mm |

| | |
|----------------------------|--------------|
| Working Temperature | -20 to 40 °C |
| Storage Temperature | -10 to 60 °C |
| IP Protection Class | IP 65 |

| | |
|----------------------------|---------|
| Life Time L70 / B50 | 35000 h |
| Switching Cycles | 15000 |

