



Housing Material	Die-cast aluminium	Storage Temperature	-10 to 60 °C
Housing Color	Grey	IP Protection Class	IP 65
Material of Lens	Glass	Life Time L70 / B50	30000 h
Protection Class	Protection class I/protective grounding	Switching Cycles	25000
Rated Input	21.5 W	Power Consumption	22 kWh/1000h
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz	Energy Efficiency Class	G
Rated Current	92 mA		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	1350 lm		
Rated Angle of Reflection	45 Degree		
Light Distribution	Symmetric		
Distribution Characteristic 120°	DLS		
Swivel Angle	180 Degree		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Top		
Length	120 mm		
Height	211 mm		
Diameter	75 mm		
Base height	37 mm		
Base diameter	99 mm		
Working Temperature	-20 to 40 °C		