



| | | | |
|--------------------------------------|-----------------------------------------------|----------------------------|--------------|
| Housing Material | Die-cast aluminium | Diameter | 112 mm |
| Housing Color | Blue | Product weight | 835 g |
| Housing Surface | Matt | Working Temperature | -20 to 40 °C |
| Material of Lens | Polycarbonate - PC | Storage Temperature | -20 to 50 °C |
| Surface Structure of Lens | Clear | IP Protection Class | IP 65 |
| Protection Class | Protection class III/safety extra-low voltage | IK Protection Class | IK04 |
| Rated Input | 3.5 W | Life Time L70 / B50 | 20000 h |
| Rated Input Voltage | 3.7 V/DC | Power Consumption | 4 kWh/1000h |
| Dimmable | Yes | | |
| Control technology | Touch-Sensor | | |
| Motion Detector | No | | |
| Accumulator/Battery Operated | Yes | | |
| Rechargeable/battery included | Yes | | |
| Number of Accumulator/Battery | 1 | | |
| Type of Accumulator/Battery | Li-Ion battery type 18650 | | |
| Accumulator/Battery Capacity | 4400 mAh | | |
| Accumulator/Battery Voltage | 3.7 V | | |
| Accumulator Charging Time | 6.5 h | | |
| Accumulator Operating Time | 8 h | | |
| Light Source | LED, Light source changeable TC | | |
| Lightcolor | Warm white (WW) | | |
| Color Temperature | 2200/3000 K | | |
| Colour Rendering Index (Ra) | 80 | | |
| Rated Luminous Flux | 270 lm | | |
| Luminous Efficiency | 77.1 lm/W | | |
| Rated Angle of Reflection | 100 Degree | | |
| Light Exit Surfaces | 1 | | |
| Light characteristics | Direct | | |
| Light direction | Below | | |
| Height | 370 mm | | |