



A modern standing lamp for office rooms with modern control technology. The minimalistic light automatically switches on if there is movement. In addition, the OFFICE THREE MOTION adapts to the daylight conditions present and regulates the brightness for relaxed working even over longer periods of time. Movement sensor and daylight sensor can be deactivated separately from each other. The direct and indirect light proportion can be controlled separately. Thanks to UGR < 6, the light is particularly glare-free and ideal for lighting up individual work spaces.

Special features

- Particularly low glare value
- Daylight and movement sensor
- Dimmable using touch panel
- High lumen output
- Direct and indirect light

Housing Material	Aluminium
Housing Color	White
Housing Surface	Matt
Material of Lens	Plastic
Protection Class	Protection class I/protective grounding
Power Selectable	55 W, 25 W
Rated Input Voltage	200-240 V/AC 50 / 60 Hz
Frequency	
Power Supply Unit incl.	No
Connection Cable Primary	Yes
Primary Connection	Power plug
Primary Cable Length	2.5 m
Connection Type According to Standard	Typ Y
Dimmable	Yes
Control technology	Touch-Sensor
Motion Detector	Yes
Kind of Motion Detector	Infrared
Detection Distance	0-3.5 m
Angle of Detection	85 Degree

Light Source	LED, Light source not changeable
Lightcolor	Neutral white
Color Temperature	4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	9600 lm
Luminous Efficiency	120 lm/W
Rated Angle of Reflection	110 Degree
Rated Angle of Reflection 2	50 Degree
UGR	6
Distribution Characteristic 120°	NDLS

Light Exit Surfaces	2
----------------------------	---

Light characteristics	Direct
Light direction	Top, Below
Length	1056 mm
Width	64 mm
Height	1950 mm
Product weight	11310 g
Working Temperature	-20 to 45 °C
Storage Temperature	-40 to 80 °C
IP Protection Class	IP 20
Life Time L70 / B50	50000 h
Life Time L80 / B10	50000 h
Switching Cycles	25000
Power Consumption	80 kWh/1000h
Energy Efficiency Class	D

