

Art. no. 950014

Pendant lamp Lautaro 600/60 Down Prism M3, 37 W,  
DALI, 3000 K, white

 **DEKO LIGHT**



|                                        |                                         |                                            |                                                                    |
|----------------------------------------|-----------------------------------------|--------------------------------------------|--------------------------------------------------------------------|
| <b>Housing Material</b>                | Aluminium, Steel                        | <b>Life Time L70 / B50</b>                 | 180000 h                                                           |
| <b>Housing Color</b>                   | White                                   | <b>Life Time L80 / B10</b>                 | 120000 h                                                           |
| <b>Material of Lens</b>                | Polycarbonate - PC                      | <b>Life Time L80 / B50</b>                 | 130000 h                                                           |
| <b>Surface Structure of Lens</b>       | Microprismatic                          | <b>Life Time L90 / B10</b>                 | 50000 h                                                            |
|                                        |                                         | <b>Life Time L90 / B20</b>                 | 60000 h                                                            |
| <b>Protection Class</b>                | Protection class I/protective grounding | <b>Switching Cycles</b>                    | 100000 PCS                                                         |
| <b>Rated Input</b>                     | 37 W                                    | <b>Power Consumption</b>                   | 37 kWh/1000h                                                       |
| <b>Rated Power Consumption Standby</b> | 0.3 W                                   | <b>Energy Efficiency Class Lightsource</b> | This product contains a light source of energy efficiency class E. |
| <b>Rated Input Voltage</b>             | 198-264 V/AC                            |                                            |                                                                    |
| <b>Dimmable</b>                        | Yes                                     |                                            |                                                                    |
| <b>Control</b>                         | DALI 2 / DT6, Push-Dim                  |                                            |                                                                    |
| <b>Light Source</b>                    | LED, Light source changeable TC         |                                            |                                                                    |
| <b>Color Temperature</b>               | 3000 K                                  |                                            |                                                                    |
| <b>Colour Consistency</b>              | 3 SDCM                                  |                                            |                                                                    |
| <b>Colour consistency light source</b> | 2 SDCM                                  |                                            |                                                                    |
| <b>CRI (Ra)</b>                        | 90                                      |                                            |                                                                    |
| <b>Rated Luminous Flux</b>             | 4600 lm                                 |                                            |                                                                    |
| <b>Rated Angle of Reflection</b>       | 90 Degree                               |                                            |                                                                    |
| <b>UGR</b>                             | 19                                      |                                            |                                                                    |
| <b>Light Exit Surfaces</b>             | 1 PCS                                   |                                            |                                                                    |
| <b>Light characteristics</b>           | Direct                                  |                                            |                                                                    |
| <b>Light direction</b>                 | Below                                   |                                            |                                                                    |
| <b>Height</b>                          | 60 mm                                   |                                            |                                                                    |
| <b>Diameter</b>                        | 600 mm                                  |                                            |                                                                    |
| <b>Pendulum Length max.</b>            | 3000 mm                                 |                                            |                                                                    |
| <b>Working Temperature</b>             | -20 to 50 °C                            |                                            |                                                                    |
| <b>Storage Temperature</b>             | -40 to 80 °C                            |                                            |                                                                    |
| <b>IP Protection Class Lamp</b>        | IP 20                                   |                                            |                                                                    |
| <b>IK Protection Class</b>             | IK05                                    |                                            |                                                                    |