



**Special features**

- Can be dimmed using trailing-edge phase dimmers
- Flicker-free
- Short circuit, overload and overheating protection

<b>Housing Material</b>	Plastic
<b>Housing Color</b>	Black
<b>Operating Mode</b>	Constant current
<b>Protection Class</b>	Protection class II/protective insulation
<b>Power</b>	6.0-12 W
<b>Output Voltage</b>	23-46 V/DC
<b>Output Current</b>	260 mA
<b>Dimmable</b>	Yes
<b>Control</b>	Trailing-edge dimmer
<b>Number of Channels</b>	1
<b>Power Factor</b>	0.96
<b>Max. units per MCB B10</b>	17
<b>Max. units per MCB B16</b>	28
<b>Max. units per MCB C10</b>	37
<b>Max. units per MCB C16</b>	59
<b>Inrush Current max.</b>	10 A / 300 μs
<b>Capacitive Load</b>	20.65 nF
<b>Reference Point Tc</b>	90 °C
<b>Working Temperature</b>	-20 to 45 °C
<b>Storage Temperature</b>	-20 to 70 °C
<b>IP Protection Class</b>	IP 20
<b>Life Time</b>	30000 h
<b>Length</b>	115 mm
<b>Width</b>	39 mm
<b>Height</b>	22 mm
<b>Product weight</b>	80 g

