



Due to their flexible control options, you can use the D PROFESSION pendant lamps both in private and in commercial applications. In private settings, the dimmable Down version creates an exceptional atmosphere of illumination that blends perfectly with its modern design.

**Special features**

- High light output
- Very low glare value
- Dimmable
- Max. suspended mounting 3,000 mm

<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	Silver
<b>Material of Lens</b>	Plastic
<b>Protection Class</b>	Protection class I/protective grounding
<b>Rated Input</b>	28 W
<b>Rated Input Voltage Frequency</b>	200-240 V/AC 50 / 60 Hz
<b>Power Supply Unit incl.</b>	Yes
<b>Connection Type</b>	Clamp
<b>Dimmable</b>	Yes
<b>Control technology</b>	Leading-edge dimmer, Trailing-edge dimmer
<b>Motion Detector</b>	No

<b>Working Temperature</b>	-20 to 40 °C
<b>Storage Temperature</b>	-30 to 60 °C
<b>IP Protection Class</b>	IP 20

<b>Life Time L70 / B50</b>	50000 h
<b>Switching Cycles</b>	25000
<b>Power Consumption</b>	28 kWh/1000h
<b>Energy Efficiency Class</b>	D

<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	4000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	3165 lm
<b>Rated Angle of Reflection</b>	24 Degree
<b>UGR</b>	19
<b>Light Distribution</b>	Symmetric
<b>Distribution Characteristic 120°</b>	DLS

<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Below

<b>Length</b>	1177.4 mm
<b>Width</b>	53 mm
<b>Height</b>	53 mm
<b>Base length</b>	560 mm
<b>Base width</b>	65 mm
<b>Base height</b>	38 mm
<b>Pendulum Length max.</b>	3000 mm

