



Housing Material	Aluminium	Base width	19 mm
Housing Color	Silver	Base height	5.3 mm
Housing Surface	Shiny	Working Temperature	-5 to 40 °C
Material of Lens	Plastic	Storage Temperature	-10 to 40 °C
Colour of Lens	White	IP Protection Class	IP 20
Surface Structure of Lens	Opal	Life Time L70 / B50	30000 h
Protection Class	Protection class II/protective insulation	Switching Cycles	15000
Rated Input	3.2 W	Power Consumption	4 kWh/1000h
Rated Input Voltage	220-240 V/AC 50 / 60 Hz	Energy Efficiency Class	G
Frequency			
Power Supply Unit incl.	Yes		
Connection Cable Primary	Yes		
Primary Connection	Power plug		
Primary Cable Length	1 m		
Connection Type According to Standard	Typ Y		
Connection Cable Secondary	Yes		
Secondary Connection	Plug mini AMP		
Secondary Cable Length	1 m		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	150 lm		
Rated Angle of Reflection	180 Degree		
Distribution Characteristic	NDLS		
120°			
Length	60 mm		
Width	54 mm		
Height	48 mm		
Base length	60 mm		