



HAR-FLEX 6P FEMALE IDC CONNECTOR

HAR-FLEX 6P FEMALE IDC CONNECTOR

WIRING TABLE

C1	WIRE	C2
1	AWG 30	1
2	AWG 30	2
3	AWG 30	3
4	AWG 30	4
5	AWG 30	5
6	AWG 30	6

HARTING P/N	Cable length(L)
33152430100373	100 ± 3
33152430200373	200 ± 5
33152430500373	500 ± 5

NOTES:

- 1.)CABLE MUST BE PERFORMED 100% CONTINUITE TEST AND HI-POT TEST.
- 2.)CABLE OPERATION TEMPERATURE: -20°C TO +105°C
- 3.)CABLE SHOULD BE PACKED BY PLASTIC BAG,THEN PUT IT INTO CARTON (QTY ACCORDING TO ACTUAL CONDITION). EXPORT CARTON SHOULD BE STICKED A LABEL WITH P/N AND QTY.

	All rights reserved Department HCS - CN HARTING Customised Solutions D-32339 Espelkamp	All Dimensions in mm	Tech. Character.	Free size tol.	According to production drawing
		Created by LINI Lin	Inspected by QINL Qin	Standardisation QINL Qin	Date 2019-08-02
Title Har-flex 6Pole,Dul-end,W/O SR,L=XXmm					Doc-Key / ECM-Nr. 100749026/UGD/007/A 500000156049
		Type TB	Number 33 15 243 XXX0373		Rev. A Page 1/1