



Equipped with LEDs in a neutral white light colour [4,000 K], the TRIPROOF LED IP65 damp-proof light consists of a light grey polycarbonate housing and a satin-finished polycarbonate cover in one piece. It is suitable for simple ceiling, wall or suspended mounting and is available in three different lengths. Several lights can be connected in series; ideal for industrial and private use, e.g. for lighting under canopies, in cellar rooms, workshops, garages, industrial halls etc. The light has a simple electrical connection with push-in connector.

**Special features**

- High impact resistance
- Feed-through wiring possible

<b>Housing Material</b>	Plastic
<b>Housing Color</b>	White
<b>Housing Surface</b>	Matt

<b>Power Consumption</b>	44 kWh/1000h
<b>Energy Efficiency Class</b>	G

<b>Protection Class</b>	Protection class II/protective insulation
<b>Rated Input</b>	44 W
<b>Rated Input Voltage Frequency</b>	180-240 V/AC 50 / 60 Hz
<b>Power Supply Unit incl.</b>	Yes
<b>Connection Type</b>	Clamp
<b>Dimmable</b>	No
<b>Motion Detector</b>	No

<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	4000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	3820 lm
<b>Rated Angle of Reflection</b>	120 Degree
<b>Distribution Characteristic 120°</b>	NDLS

<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Below

<b>Length</b>	1598 mm
<b>Width</b>	61 mm
<b>Height</b>	56 mm

<b>Working Temperature</b>	-20 to 40 °C
<b>Storage Temperature</b>	-10 to 60 °C
<b>IP Protection Class</b>	IP 65

<b>Life Time L70 / B50</b>	35000 h
<b>Switching Cycles</b>	15000

