



Equipped with LEDs in a neutral white light colour [4,000 K], the TRIPROOF LED IP65 damp-proof light consists of a light grey polycarbonate housing and a satin-finished polycarbonate cover in one piece. It is suitable for simple ceiling, wall or suspended mounting and is available in three different lengths. Several lights can be connected in series; ideal for industrial and private use, e.g. for lighting under canopies, in cellar rooms, workshops, garages, industrial halls etc. The light has a simple electrical connection with push-in connector.

Special features

- High impact resistance
- Feed-through wiring possible

Housing Material	Plastic
Housing Color	White
Housing Surface	Matt
Protection Class	Protection class II/protective insulation
Rated Input	18.5 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	No
Motion Detector	Yes
Kind of Motion Detector	Infrared
Detection Distance	2.5-10 m
Angle of Detection	360 Degree

IK Protection Class	IK08
Life Time L70 / B50	30000 h
Switching Cycles	15000
Power Consumption	19 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	1900 lm
Rated Angle of Reflection	120 Degree
Distribution Characteristic 120°	NDLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Length	665 mm
Width	61 mm
Height	56 mm

Working Temperature	-20 to 45 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 65

