



It takes a lot to catch the Altais series off guard. Thanks to IP54 and impact strength class IK10, these slender outdoor lights are impressive all rounders both in a commercial and private setting. The Altais lights offer additional flexibility with their integrated movement sensor [programmable using remote control] and the adjustable light colour for different lighting scenarios.

Special features

- Light colour adjustable in 3 stages
- High impact resistance
- Splash water protected

Housing Material	Plastic	Life Time L70 / B50	50000 h
Housing Color	White	Switching Cycles	75000
Protection Class	Protection class II/protective insulation	Power Consumption	12 kWh/1000h
Rated Input	12 W	Energy Efficiency Class	E
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Connection Type	Clamp		
Dimmable	No		
Motion Detector	Yes		
Kind of Motion Detector	High frequency		
Detection Distance	1-12 m		
Angle of Detection	150 Degree		
Light Source	LED, Light source not changeable		
Color Temperature	3000/4000/6000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	85		
Rated Luminous Flux	1260 lm		
Rated Angle of Reflection	120 Degree		
Distribution Characteristic 120°	NDLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Height	48 mm		
Diameter	220 mm		
Working Temperature	-40 to 50 °C		
Storage Temperature	-10 to 60 °C		
IP Protection Class	IP 54		
IK Protection Class	IK10		