



Our new SUBRA lights cut a fine figure whether ceiling- or wall-mounted. This is ensured not only by the low assembly height of just 7 cm but also by the circumferential light ring, which functions as an additional design element. The SUBRA offers added sophistication when it comes to dimming. There is TRIAC [analogue] and DALI [digital] to choose from - both for the warm white and neutral white versions. There is also a variant with an integrated, adjustable movement sensor.

**Special features**

- Light ring as design element
- Easy to install using clip connection
- High light output
- Splash water protected for ceiling installation

<b>Housing Material</b>	Aluminium
<b>Housing Color</b>	White
<b>Material of Lens</b>	Plastic
<b>Colour of Lens</b>	White
<b>Protection Class</b>	Protection class II/protective insulation
<b>Rated Input</b>	29 W
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz
<b>Power Supply Unit incl.</b>	Yes
<b>Connection Type</b>	Clamp
<b>Dimmable</b>	Yes
<b>Control technology</b>	DALI 1 / DT6
<b>Motion Detector</b>	No

<b>IP Protection Class</b>	IP 54
<b>IK Protection Class</b>	IK10
<b>Life Time L70 / B50</b>	50000 h
<b>Switching Cycles</b>	40000
<b>Power Consumption</b>	29 kWh/1000h
<b>Energy Efficiency Class</b>	F

<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	3000 K
<b>Colour Consistency</b>	6 SDCM
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	2636 lm
<b>Rated Angle of Reflection</b>	110 Degree
<b>Light Distribution</b>	Symmetric
<b>Distribution Characteristic 120°</b>	DLS

<b>Light Exit Surfaces</b>	2
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Below, Side

<b>Height</b>	70 mm
<b>Diameter</b>	350 mm
<b>Base height</b>	22 mm
<b>Base diameter</b>	290 mm

<b>Working Temperature</b>	-10 to 40 °C
<b>Storage Temperature</b>	-10 to 60 °C