



Housing Material	Aluminium	Height	370 mm
Housing Color	Green	Diameter	112 mm
Surface structure	Matt	Product weight	11995 g
Material of Lens	Polycarbonate - PC	Working Temperature	-20 to 40 °C
Surface Structure of Lens	Clear	Storage Temperature	-20 to 50 °C
Functions	Nightsaver	IP Protection Class	IP 65
Protection Class	Protection class III/safety extra-low voltage	IK Protection Class	IK04
Rated Input	3.5 W	Power Consumption	4 kWh/1000h
Rated Input Voltage	3.7 V/DC		
Power Supply Unit incl.	No		
Dimmable	Yes		
Control	Touch-Sensor		
Motion Detector	No		
Accumulator/Battery Operated	Yes		
Rechargeable/battery included	Yes		
Number of Accumulator/Battery	1 PCS		
Type of Accumulator/Battery	Li-Ion battery type 18650		
Accumulator/Battery Capacity	4400 mAh		
Accumulator/Battery Voltage	3.7 V		
Accumulator Charging Time	6.5 h		
Accumulator Operating Time	8 h		
Light Source	LED, Light source changeable TC		
Lightcolor	Warm white (WW)		
Color Temperature	2200/3000 K		
CRI (Ra)	80		
Rated Luminous Flux	270 lm		
Luminous Efficiency	77.1 lm/W		
Rated Angle of Reflection	100 Degree		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		