





The copying, distribution and utilization of this document as well as the communication of the contents to others without expressed authorization is prohibited according to §18 UWG German Law. Offenders will be held liable for the payment of damages according to §19 UWG German Law. All rights reserved, in particular the right to carry out patent, utility model or ornamental design registrations.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts gem. §18 UWG verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz (§19 UWG). Alle Rechte vorbehalten, insbesondere das Recht, Patent-, Gebrauchsmuster- oder Geschmacksmusteranmeldungen durchzuführen. PHOENIX CONTACT Connector Technology GmbH Heisenbergstrasse 1 D-71083 Herrenberg

Mechanical data (according to IEC 61076-2-101)	
Locking thread	M12 Standard
Material	
Flange housing	brass, nickel-plated
Sealing gasket	-
Temperature range	-40 °C to +85 °C

further information:
- see installation recommendation SACC-M12 NUT PRESS



general tolerance acc. to DIN ISO 2768-c			technical changes reserved		Index 0 / 2018-08-01		scale: 2:1		
	date	name	Series DSIV M12 housing screw connection female Ø16 / press-in version					page: 1 of: 1	
design	2018-08-01	Scheerer							
chk.									
			drawing-no.:	BS-00000006C1K		doc.-no.:	01156684		
			order-no.:	1087027					
			article designation:	SACC-M12 NUT PRESS WO/VPE 500					