

MATRIC FX | SYSTEM 40MM RECESSED FRAME

1. MONTAGE UND INSTALLATION | MOUNTING AND INSTALLATION:

First diffuser removal

PULL

1. Bei allen Montagearbeiten Handschuhe tragen.
 Use gloves when handling the fixture.

Opal / Microprismatic / Wallwasher		Lens Louver	
L[mm]	L1[mm]	L[mm]	L1[mm]
610	604	675	669
900	894	940	934
1192	1186	1204	1198
1485	1479	1468	1462
1775	1769	1733	1727
2065	2059	1997	1991

2. Montageöffnungen.
 Installation openings.

Diffuser removal

CREDIT CARD

LED insets locking system

PULL

The foil inserted into the Microprismatic screen has a diffusion function - do not remove it!

3.

L4	120 mm
L5	12 - 28 mm

4.

1 UNLOCKED

2 LOCKED

3

5. Luminaire not suitable for covering with thermally insulating material.

6.

- min/max stripped wire length: 7mm-10mm

- max power supply cable: 1,5mm²

1

2

CLICK

7. All LED gear trays are numbered and the numbering starts from the cable entry side. In non-standard luminaires the numbering of LED gear trays is made in accordance with technical drawings.
 Avoid touching the strip - connectors because they can break off under excess handling.

CLICK

8.

CLICK

9. Lens louver installation.

MATRIC FX | SYSTEM 40MM RECESSED FRAME WALLWASHER

Wall-washer
diffuser removal

10. Bei allen Montagearbeiten Handschuhe tragen.
 Use gloves when handling the fixture.

11.

12. Luminaire not suitable with
thermally insulating material.

13.

14.

- min/max stripped wire length: 7mm-10mm

- max power supply cable: 1,5mm²

15.

CLICK