

har-SAB M12/4/4p PAC 5m PUR



Image is for illustration purposes only. Please refer to product description.

Identification

| | |
|---------------|---|
| Series | Circular connectors M12 |
| Element | Distribution boxes |
| Specification | Pre-assembled master cable With LED green/yellow |

Version

| | |
|-----------------------|---|
| Cable length | 5 m |
| Core structure | 3x 0.75 mm ² + 4x 0.34 mm ² |
| Total number of ports | 4 |
| Number of contacts | 4 |

Technical characteristics

| | |
|--|--------------------|
| Rated current | 9 A |
| Rated voltage | 10 V DC 30 V DC |
| Limiting temperature | -30 ... +85 °C |
| Degree of protection acc. to IEC 60529 | IP67 |
| Number of channels per port | 1 |
| Circuit logic | PNP |

Material properties

| | |
|------------------|--------------------|
| Material (cable) | PUR (polyurethane) |
| RoHS | compliant |
| ELV status | compliant |

Material properties

| | |
|--------------------------------------|---------------|
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Nickel |

Specifications and approvals

| | |
|----------|---|
| UL / CSA | UL 2238 CYJV.E500416 CSA-C22.2 CYJV7.E500416 |
|----------|---|

Commercial data

| | |
|--------------------------------|---|
| Packaging size | 1 |
| Country of origin | China |
| European customs tariff number | 85444290 |
| GTIN | 5713140276963 |
| eCl@ss | 27440108 Passive Sensor-Actuator-Interface (with cable) |
| ETIM | EC002585 |
| UNSPSC 24.0 | 31251501 |