

**Product Features**

PoE Power Supply for DIN-rail mounting, Output Power 80W, for up to 3 PoE+ devices (class 0-4), width 118mm, lightgrey (similar RAL 7035)

- for DIN rail mounting (108 mm)
- protection class IP20 (DIN EN 60529)
- detachable, screwless plug-in terminal up to 2,5mm diameter with 230 V
- integrated power supply, 100-240 V / 50-60 Hz
- power consumption (free state): <0,5 W
- automated short-circuit and overload protective device
- Operating temperature: -20°C to +45°C
- detachable, screwless plug-in terminal up to 1,5mm diameter with PoE
- output voltage: 52 V
- output power: 80 W
- for up to 3 PoE+ devices (Class 0-4)
- LEDs for operation indication
- 230V: 3-pole detachable terminal block
- PoE: 2-pole detachable terminal block
- power consumption (free state): <0,5 W

Features

General	
Protection class IP	20
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921663646
Mounting types	
DIN-Rail	Yes
Dimensions/Weights without packaging	
Length mm	108
Width mm	90
Height mm	64
Net weight piece kg	0,276
Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes

Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	0,328
Packaging unit Width mm	100
Packaging unit Height mm	116
Packaging unit Depth mm	76
References	
Accessories	13910200, 23510201, 23510202, 23510504, 23810200
Similar article	23510306

