

Panel mounting socket outlet, straight - flange 120x120, fixing centers 100x100




Product description	
BALS-Prd.-Nr	13451
EAN	4024941134514
Product category	Panel mounting socket outlet, straight
Current	125A
Number of poles	5p
Poles	3p+N+PE
Position of earth contact	6 h
Voltage	200/346 up to 240/415V

Product description	
Frequency	50 and 60Hz
Protection degree	IP67
Colour code	red RAL 3000
Colour of appliance	Hinged lid red RAL 3000, Bayonet ring grey RAL 7035, Enclosure grey RAL 7035
Connection design	screw terminal as box terminal with Kontex-contact
Maximum conductor size	70.0 qmm
Cable entry	other
Height	129mm
Width	125mm
Depth	166mm
Flange size vertical	120mm
Flange size horizontal	120mm
Drill hole distance vertical	100mm
Drill hole distance horizontal	100mm
Material of enclosure	Polyamide
Contact	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Logistics data	
Weight/pcs	1.125 kg / Piece
Packaging	Bag

Logistics data	
Content amount	1 ST
EAN	4024941134514
Length	166 mm
Width	125 mm
Height	129 mm
Weight	1.126 kg
Volume	2,676.75 ccm
Packaging	Carton
Content amount	5 ST
EAN	4024941945981
Length	330 mm
Width	216 mm
Height	260 mm
Weight	5.851 kg
Volume	17,062.5 ccm

 4 MB 55	Ampere	125	125	125			
	Polzahl	3	4	5			
	a	120,0	120,0	120,0			
	b	120,0	120,0	120,0			
	c	100,0	100,0	100,0			
	d	100,0	100,0	100,0			
	e ø	6,5	6,5	6,5			
	f	21,0	21,0	21,0			
	h	50,0	50,0	50,0			
	i	117,0	117,0	117,0			
	k	129,0	129,0	129,0			
	l ø	104,0	104,0	104,0			
	m	6,0	6,0	6,0			
	Leiter mm ² min	25	25	25			
	Leiter mm ² max	70	70	70			