



<b>Housing Material</b>	Aluminium, Polycarbonate, Iron	<b>Life Time L70 / B50</b>	30000 h
<b>Housing Color</b>	Black	<b>Switching Cycles</b>	20000
<b>Housing Surface</b>	Matt	<b>Power Consumption</b>	65 kWh/1000h
<b>Material of Lens</b>	Acryl	<b>Energy Efficiency Class Lightsource</b>	This product contains light sources of energy efficiency classes E and F.
<b>Surface Structure of Lens</b>	Satined		
<b>Protection Class</b>	Protection class I/protective grounding		
<b>Rated Input</b>	65 W		
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Dimmable</b>	Yes		
<b>Control technology</b>	Leading-edge dimmer, Trailing-edge dimmer		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source changeable TC		
<b>Color Temperature</b>	3000/4000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	5600/6000 lm		
<b>Rated Luminous Flux 2</b>	6000 lm		
<b>Light Exit Surfaces</b>	2		
<b>Light characteristics</b>	Direct, Indirect		
<b>Light direction</b>	Top, Below		
<b>Height</b>	90 mm		
<b>Diameter</b>	600 mm		
<b>Working Temperature</b>	-10 to 45 °C		
<b>Storage Temperature</b>	-10 to 45 °C		
<b>IP Protection Class</b>	IP 20		