



Housing Material	Aluminium, Steel	Life Time L70 / B50	180000 h
Housing Color	Light grey	Life Time L80 / B10	120000 h
Material of Lens	Polycarbonate - PC	Life Time L80 / B50	130000 h
Surface Structure of Lens	Opal	Life Time L90 / B10	50000 h
		Life Time L90 / B20	60000 h
Protection Class	Protection class I/protective grounding	Switching Cycles	100000 PCS
Rated Input	37 W	Power Consumption	37 kWh/1000h
Rated Power Consumption Standby	0.3 W	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class E.
Rated Input Voltage	198-264 V/AC		
Dimmable	Yes		
Control	DALI 2 / DT6, Push-Dim		
Light Source	LED, Light source changeable TC		
Color Temperature	3000 K		
Colour Consistency	3 SDCM		
Colour consistency light source	2 SDCM		
CRI (Ra)	90		
Rated Luminous Flux	4450 lm		
Rated Angle of Reflection	90 Degree		
UGR	22		
Light Exit Surfaces	1 PCS		
Light characteristics	Direct		
Light direction	Below		
Height	60 mm		
Diameter	600 mm		
Pendulum Length max.	3000 mm		
Working Temperature	-20 to 50 °C		
Storage Temperature	-40 to 80 °C		
IP Protection Class Lamp	IP 20		
IK Protection Class	IK05		