

DSUB SV MA SSDP STR29 37P PL2NUT4-40HT



Image is for illustration purposes only. Please refer to product description.

| Part number | 09 65 429 6702 |
|--------------------|---|
| Specification | DSUB SV MA SSDP STR29 37P PL2NUT4-40HT |
| HARTING eCatalogue | https://b2b.harting.com/09654296702 |

Identification

| Category | Connectors |
|----------------------------|---------------------|
| Series | D-Sub |
| Identification | Standard |
| Element | Connector |
| Description of the contact | Stamped Straight |

Version

| Termination method | Reflow soldering termination (THR) |
|--------------------|---------------------------------------|
| Gender | Male |
| Size | D-Sub 4 |
| Connection type | Motherboard to daughtercard Mezzanine |
| Number of contacts | 37 |
| Termination length | 2.9 mm |
| Locking type | Fixing flange with thread 4-40 UNC |

Technical characteristics

| Distance between rows | 2.84 mm |
|------------------------------------|---------------------|
| Contact spacing (termination side) | 2.76 mm |
| Rated current | 6.5 A |
| Clearance distance | ≥1 mm |
| Creepage distance | ≥1 mm |
| Insulation resistance | >10 ¹⁰ Ω |



Technical characteristics

| Contact resistance | ≤10 mΩ |
|----------------------------------|---|
| Tightening torque | ≤0.6 Nm Female screw lock |
| Limiting temperature | -55 +125 °C (during reflow soldering max. +240 °C for 15 s) |
| Insertion force | ≤123 N |
| Withdrawal force | ≥11 N ≤82 N |
| Performance level | 2 acc. to CECC 75301-802 |
| Mating cycles | ≥250 |
| Test voltage U _{r.m.s.} | 1 kV |
| Isolation group | II (400 ≤ CTI < 600) |
| PCB thickness | ≥1.6 mm |
| Installation height | 6.2 mm |
| Hot plugging | No |

Material properties

| Material (insert) | Thermoplastic resin, glass-fibre filled (PCT) Shell: steel, nickel plated |
|---|---|
| Colour (insert) | Grey |
| Material (contacts) | Copper alloy |
| Surface (contacts) | Noble metal over Ni |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | е |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead Nickel |
| Requirement set with Hazard Levels | R26 |



Specifications and approvals

eCl@ss

| Specifications | DIN 41652 |
|--------------------------------|---------------|
| Commercial data | |
| Packaging size | 50 |
| Net weight | 15.62 g |
| Country of origin | Romania |
| European customs tariff number | 85366990 |
| GTIN | 5713140079236 |

27440214 D-Sub coupler