

## Han-Modular Compact top entry M25



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 14 001 0401                                                                        |
| Specification      | Han-Modular Compact top entry M25                                                     |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19140010401">https://b2b.harting.com/19140010401</a> |

### Identification

|                          |                      |
|--------------------------|----------------------|
| Category                 | Hoods/Housings       |
| Series of hoods/housings | Han-Modular® Compact |
| Type of hood/housing     | Hood                 |

### Version

|               |                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Size          | Modular Compact                                                                                                                                                                                                                                                                                                                                                                                   |
| Version       | Top entry                                                                                                                                                                                                                                                                                                                                                                                         |
| Cable entry   | 1x M25                                                                                                                                                                                                                                                                                                                                                                                            |
| Locking type  | Single locking lever                                                                                                                                                                                                                                                                                                                                                                              |
| Details       | <p>Rated voltage ≤630 V<br/>Rated impulse voltage ≤6 kV<br/>Pollution degree 3</p> <p>For a complete connector the specified voltage rating is the maximum level which can be achieved. In cases where the used module(s) do offer lower voltage ratings, then these lower ratings are valid. Higher voltage ratings in individual applications can be approved in coordination with HARTING.</p> |
| Pack contents | 4 screws are included within the delivery                                                                                                                                                                                                                                                                                                                                                         |

### Technical characteristics

|                                        |                       |
|----------------------------------------|-----------------------|
| Tightening torque                      | 1 Nm Fixing screws M3 |
| Limiting temperature                   | -40 ... +125 °C       |
| Mating cycles                          | ≥500                  |
| Degree of protection acc. to IEC 60529 | IP65 locked condition |



**Pushing Performance**  
Since 1945

## Material properties

|                                      |                |
|--------------------------------------|----------------|
| Material (hood/housing)              | Zinc die-cast  |
| Surface (hood/housing)               | Nickel plated  |
| RoHS                                 | compliant      |
| ELV status                           | compliant      |
| China RoHS                           | e              |
| REACH Annex XVII substances          | Not contained  |
| REACH ANNEX XIV substances           | Not contained  |
| REACH SVHC substances                | Not contained  |
| California Proposition 65 substances | Yes            |
| California Proposition 65 substances | Lead<br>Nickel |

## Specifications and approvals

|                |           |
|----------------|-----------|
| Specifications | IEC 61984 |
| CE             | Yes       |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 93 g                                     |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| GTIN                           | 5713140124240                            |
| eCl@ss                         | 27440202 Shell for industrial connectors |