



Product Features

1.2GB WIFI access point PoE, flush-mounted, with RJ45 front port, pure white (similar to RAL 9010)

- front RJ45 port for a data terminal
- mounting in conventional 2-gang installation pots
- nominal operating voltage: PoE (Class 0)
- power consumption: 5,5 VA typ.
- temperature range: -5°C - 35° C
- RJ45 - opening at the frontside for one data equipment
- front RJ45 port for a data terminal
- indication of functions at illuminated RJ45 -outlet
- connection of data Cable and Power supply via detachable screw terminals on the frontside
- transmission rate RJ45: 100Mbit/s
- transmission rate data cable: 1000 Mbit/s
- transmission rate RJ45: 100Mbit/s
- radio standards: IEEE 802.11 b/g/n/ac (Wave 2)
- frequency/data rate: 2,4 GHz / 5 GHz, 300 Mbit/s / 876 Mbit/s (Dualmode)
- safety and encryption: WPA, WPA2, MAC-Filter
- with timer and time-switching function
- guest WiFi additional
- central management
- reset via reset - magnet
- mesh-functionality
- suitable for the UAE-design wall plates of all well-known manufacturer (Berker, Busch-Jäger, GIRA, JUNG, Merten etc.)

Features

General	
Surface	high-gloss
Support ring	Yes
Design capability	Yes
Protection class IP	20
Halogen Free	Yes
Country of manufacture	DE
GTIN (EAN)	4043921665800
Mounting types	
flush-mounted, 2-gang Box	Yes

Up-Accesspoint UAE PoE 2,4/5GHz 1,2G rw Up 0

Article no.: 226104061

Color: purewhite (ähnlich RAL-Nr. 9010)

Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging unit Quantity	1
References	
Accessories	39200010
Similar article	226104030, 226104031, 226104032, 226104050, 22610406, 226104062, 22610408, 22610410

