



**Special features**

- Can be dimmed using leading-edge/trailing-edge phase dimmers
- Flicker-free
- Short-circuit-proof, overload protection, overheating protection

<b>Housing Material</b>	Plastic
<b>Housing Color</b>	Black
<b>Operating Mode</b>	Constant current
<b>Protection Class</b>	Protection class II/protective insulation
<b>Power</b>	9.8-22 W
<b>Output Voltage</b>	14-35 V/DC
<b>Output Current</b>	700 mA
<b>Dimmable</b>	Yes
<b>Control</b>	Trailing-edge dimmer
<b>Number of Channels</b>	1
<b>Power Factor</b>	0.97
<b>Connection Type</b>	Clamp
<b>Number of Circuit Breaker B10A max.</b>	11
<b>Number of Circuit Breaker B16A max.</b>	18
<b>Number of Circuit Breaker C10A max.</b>	24
<b>Number of Circuit Breaker C16A max.</b>	39
<b>Inrush Current max.</b>	15 A / 300 µs
<b>Capacitive Load</b>	30.67 nF
<b>Reference Point Tc</b>	90 °C
<b>Working Temperature</b>	-20 to 45 °C
<b>Storage Temperature</b>	-20 to 70 °C
<b>IP Protection Class</b>	IP 20
<b>Life Time</b>	30000 h
<b>Length</b>	127 mm
<b>Width</b>	44 mm
<b>Height</b>	28 mm
<b>Product weight</b>	113 g

