

DIN-Signal 2C/2R shroud screwfix 9.10



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 23 000 9963 |
| Specification | DIN-Signal 2C/2R shroud screwfix 9.10 |
| HARTING eCatalogue | https://b2b.harting.com/09230009963 |

Identification

| | |
|------------------------------|--|
| Category | Accessories |
| Series | DIN 41612 |
| Type of accessory | Pin shroud |
| Description of the accessory | for female connectors type 2C for male connectors type 2R |
| Features | lead-free |

Version

| | |
|--------------------|--------------|
| Termination length | 16.2 mm |
| | 17 mm |
| | 20 mm |
| Fixing | Screw fixing |

Technical characteristics

| | |
|-----------------|-------------------------------|
| Isolation group | IIIa ($175 \leq CTI < 400$) |
| PCB thickness | 2.6 mm ± 0.5 |
| | 3.4 mm ± 0.5 |
| | 6.4 mm ± 0.5 |

Material properties

| | |
|---|------------------------|
| Material (accessories) | Thermoplastic |
| Colour (accessories) | RAL 7032 (pebble grey) |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |



Pushing Performance
Since 1945

Material properties

| | |
|--------------------------------------|---------------|
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |

Specifications and approvals

| | |
|------------------------|------------------------------|
| Railway classification | F1/I2 acc. to NFF 16-101/102 |
|------------------------|------------------------------|

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 100 |
| Net weight | 3.78 g |
| Country of origin | China |
| European customs tariff number | 85389099 |
| GTIN | 5713140041332 |
| eCl@ss | 27440292 Connector component (accessories) |