




LED surface-mounted spot BLOKK, IP65

Artikel-Nr. 60112103



LED surface-mounted spot BLOKK, IP65, graphite, square. Surface mounting, Floor-mounted Mounting method: Surface mounting, Place of installation: Floor-mounted, Material: Aluminium / Glass, Degree of protection: according to DIN EN 60529 IP65, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 21W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 1.600lm, Colour temperature: 3.000 K, Beam angle: 32°, Adjustability: Pivoted, With control gear: Yes, Control: on/off.

Artikel-Nr.	60112103
Stand:	25.10.2021 19:50

Colour temperature	3000K
Colour	Graphite
McAdam-Step	McAdam-Step 3
Amount of light sources / fittings	1 Qty
Material	Aluminium / Glass
Power	21 W
Lamp	LED
scope of delivery	Incl. converter for connection to the 230-V mains voltage, on/off and 2,000 mm connecting cable

Colour rendering	CRI > 80
Control	on/off
Voltage	230V AC 50Hz
Degree of protection	IP65
Protection class	I
Adjustability	Pivoted
Length	110 mm
Width	110 mm
Aufbauhöhe	160 mm
Swivel angle	90 °
Circuit type	Parallel conduction