

**Special features**

- Adjustable panel
- Base L x W x H: 185 x 63 x 105 mm

Housing Material	Die-cast aluminium
Housing Color	Grey
Material of Lens	Plastic
Protection Class	Protection class I/protective grounding
Rated Input	13.5 W
Rated Input Voltage Frequency	100-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	No
Motion Detector	No

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	370 lm
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Swivel Angle	90 Degree
Light Exit Surfaces	1
Light characteristics	Direct, Indirect
Light direction	Below

Length	223 mm
Width	130 mm
Height	105 mm
Diameter	105 mm
Base length	185 mm
Base width	63 mm
Base height	30 mm

Working Temperature	-20 to 40 °C
----------------------------	--------------

Storage Temperature	-10 to 60 °C
IP Protection Class	IP 65
Life Time L70 / B50	30000 h
Switching Cycles	20000
Power Consumption	14 kWh/1000h
Energy Efficiency Class	G