



<b>Housing Material</b>	Die-cast aluminium
<b>Housing Color</b>	Blue, Black
<b>Housing Surface</b>	Matt
<b>Material of Lens</b>	Polycarbonate - PC
<b>Surface Structure of Lens</b>	Clear
<b>Protection Class</b>	Protection class III/safety extra-low voltage
<b>Rated Input</b>	2.3 W
<b>Rated Input Voltage</b>	3.7 V/DC
<b>Dimmable</b>	Yes
<b>Control technology</b>	Touch-Sensor
<b>Motion Detector</b>	No
<b>Accumulator/Battery Operated</b>	Yes
<b>Number of Accumulator/Battery</b>	1
<b>Type of Accumulator/Battery</b>	3.7 V lithium ion battery (903050)
<b>Accumulator/Battery Capacity</b>	3000 mAh
<b>Accumulator/Battery Voltage</b>	3.7 V
<b>Accumulator Charging Time</b>	4.5 h
<b>Accumulator Operating Time</b>	8 h

<b>Working Temperature</b>	-20 to 40 °C
<b>Storage Temperature</b>	-20 to 50 °C
<b>IP Protection Class</b>	IP 65
<b>IK Protection Class</b>	IK04

<b>Life Time L70 / B50</b>	20000 h
<b>Power Consumption</b>	3 kWh/1000h

<b>Light Source</b>	LED, Light source changeable TC
<b>Lightcolor</b>	Warm white (WW)
<b>Color Temperature</b>	2200/3000 K
<b>Colour Rendering Index (Ra)</b>	80
<b>Rated Luminous Flux</b>	110 lm
<b>Luminous Efficiency</b>	47.8 lm/W

<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Below

<b>Height</b>	208 mm
<b>Diameter</b>	76 mm
<b>Product weight</b>	437 g