



Special features

- Including 1.2 m connecting cable with IP44 shaped plug

Housing Material	Die-cast aluminium	Storage Temperature	-10 to 60 °C
Housing Color	Silver	IP Protection Class Lamp	IP 65
Material of Lens	Glass	IP Protection Class Plug	IP 44
		IK Protection Class	IK08
Protection Class	Protection class I/protective grounding		
Rated Input	50 W	Life Time L70 / B50	30000 h
Rated Input Voltage	220-240 V/AC 50 / 60 Hz	Switching Cycles	150000
Frequency		Power Consumption	50 kWh/1000h
Power Supply Unit incl.	Yes	Energy Efficiency Class	E
Connection Cable Primary	Yes		
Primary Connection	Power plug IP44		
Primary Cable Length	1.2 m		
Connection Type According to Standard	Typ Y		
Dimmable	No		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	4000 K		
Colour Consistency	5 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	6500 lm		
Rated Angle of Reflection	100 Degree		
UGR	28		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Length	326 mm		
Width	245 mm		
Height	40 mm		
Working Temperature	-20 to 40 °C		