

## Han 24B-HTE-PFT-DL-w/o. thread

	Part number	09 30 024 1101
	Specification	Han 24B-HTE-PFT-DL-w/o. thread

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han® B
Type of hood/housing	Panel feed through housing
Type	High construction

### Version

Size	24 B
Version	Without cable entry
Locking type	Double locking lever
Han-Easy Lock®	Yes
Field of application	Standard hoods/housings for industrial connectors

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65

### Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)
Material (seal)	NBR
Material (locking)	Polycarbonate (PC) Stainless steel

## Material properties

Colour (locking) RAL 7037 (dust grey)

Material flammability class acc. to UL 94  
(locking levers) V-0

## Specifications and approvals

Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
CE	Yes

## Commercial data

Packaging size	1
Net weight	487 g
Country of origin	China
European customs tariff number	85366990
eCl@ss	27440202 Shell for industrial connectors