## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: nobilé

Supplier's address: Produktmanagement, Wächtersbacher Str. 78, 60386 Frankfurt am Main, DE

## Model identifier: 1856865323

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS		
Light source cap-type	sonstige				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	Nein		
Colour-tuneable light source:	Nein	Envelope:	-		
High luminance light source:	Nein				
Anti-glare shield:	Nein	Dimmable:	Yes		
Product parameters					

Product parameters						
Parameter	Value	Parameter	Value			
General product parameters:						
Energy consumption in mode (kWh/1000 h), roun up to the nearest integer		Energy efficiency class	F			
Useful luminous flux (φu indicating if it refers to the in a sphere (360 <sup>9</sup> ), in a v cone (120 <sup>9</sup> ) or in a narrow o (90 <sup>9</sup> )	flux cone (90°) vide	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000			
On-mode power ( expressed in W	P <sub>on</sub> ), 8,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00			
Networked standby power ( for CLS, expressed in W rounded to the second deci	and	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	90			
Outer Height	88	Spectral power	See image			
dimensions Width	88	distribution in the	in last page			
without Depth	29					
I .	1	1	Seite 1 /			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	lf yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,436 0,404			
Parameters for directional light sources:						
Peak luminous intensity (cd)	1 400	Beam angle in degrees, or the range of beam angles that can be set	38			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	68	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-' : not applicable;

(b)<sub>'-'</sub> : not applicable;

