



Special features

- Including connecting cable

Housing Material	Stainless steel, Aluminium
Housing Color	Silver
Material of Lens	Glass
Protection Class	Protection class I/protective grounding
Rated Input	18 W
Rated Input Voltage Frequency	220-240 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Cable Primary	Yes
Primary Connection	Connection box
Primary Cable Length	0.5 m
Dimmable	No
Motion Detector	No

Product weight	3170 g
Working Temperature	-20 to 40 °C
Storage Temperature	-10 to 60 °C
IP Protection Class	IP 67
IK Protection Class	IK07
Load Force max.	20 kN

Life Time L70 / B50	35000 h
Switching Cycles	20000
Power Consumption	19 kWh/1000h
Energy Efficiency Class	G

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	1100 lm
Luminous Efficiency	61.1 lm/W
Rated Angle of Reflection	20 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Top

Length	549 mm
Width	68 mm
Height	31.5 mm
Installation Depth	80 mm
Cut Out Length	527 mm
Cut Out Width	68 mm