



Pushing Performance
Since 1945

Han ES 10B PE-CC Male



| | |
|--------------------|---|
| Part number | 09 33 010 2676 |
| Specification | Han ES 10B PE-CC Male |
| HARTING eCatalogue | https://b2b.harting.com/09330102676 |

Identification

| | |
|---------------|--|
| Category | Inserts |
| Series | Han® ES |
| Specification | Cage clamp termination for PE connection |

Version

| | |
|--------------------|------------------------|
| Termination method | Cage-clamp termination |
| Gender | Male |
| Size | 10 B |
| Number of contacts | 10 |
| PE contact | Yes |

Technical characteristics

| | |
|---------------------------|------------------------------|
| Conductor cross-section | 0.14 ... 2.5 mm ² |
| Conductor cross-section | AWG 26 ... AWG 14 |
| Rated current | 16 A |
| Rated voltage | 500 V |
| Rated impulse voltage | 6 kV |
| Pollution degree | 3 |
| Rated voltage acc. to UL | 600 V |
| Rated voltage acc. to CSA | 600 V |
| Insulation resistance | >10 ¹⁰ Ω |
| Contact resistance | ≤3 mΩ |
| Stripping length | 7 ... 9 mm |
| Limiting temperature | -40 ... +125 °C |



Pushing Performance
Since 1945

Technical characteristics

| | |
|---------------|------|
| Mating cycles | ≥500 |
|---------------|------|

Material properties

| | |
|---|------------------------|
| Material (insert) | Polycarbonate (PC) |
| Colour (insert) | RAL 7032 (pebble grey) |
| Material (contacts) | Copper alloy |
| Surface (contacts) | Silver plated |
| Material flammability class acc. to UL 94 | V-0 |

Specifications and approvals

| | |
|----------------|---|
| Specifications | IEC 60664-1 IEC 61984 |
| Approvals | DNV GL |
| UL / CSA | UL 1977 ECBT2.E235076 UL 2237 PVVA2.E318390 CSA-C22.2 No. 182.3 PVVA8.E318390 |

Commercial data

| | |
|--------------------------------|---|
| Packaging size | 1 |
| Net weight | 64.5 g |
| Country of origin | China |
| European customs tariff number | 85366990 |
| GTIN | 5713140186125 |
| eCl@ss | 27440205 Contact insert for industrial connectors |