



Special features

- integrated power supply unit for 230V direct connection
- with motion detector
- through-wiring possible
- power adjustable in 2 stages
- suitable for 68 mm switch boxes of normal and deep design

Housing Material	Aluminium, Polycarbonate
Housing Color	White
Protection Class	Protection class I/protective grounding
Power Selectable	2 W, 4 W
Rated Power Consumption	0.5 W
Standby	
Rated Input Voltage	220-240 V/AC 50 / 60 Hz
Frequency	
Power Supply Unit incl.	Yes
Number of Cable Entries	3 PCS
Dimmable	No
Motion Detector	Yes
Kind of Motion Detector	Infrared
Detection Distance	3-3 m
Angle of Detection	120 Degree
Motion detector changeable	Yes
Adjustable brightness threshold	No
Adjustable follow-up time	No
Light Source	LED, Light source not changeable
Color Temperature	2700 K
Colour Consistency	3 SDCM
Colour consistency light source	3 SDCM
Colour Rendering Index (Ra)	80
Rated Luminous Flux	610 lm
Luminous Efficiency	105 lm/W
UGR	19
Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Front
Height	41 mm

Diameter	71.5 mm
Installation Depth	39 mm
Required Installation Depth	60 mm
Cut Out Diameter	68 mm
Product weight	90 g
Working Temperature	-20 to 40 °C
Storage Temperature	-40 to 80 °C
IP Protection Class	IP 20
IK Protection Class	IK05
Life Time L70 / B50	132000 h
Life Time L80 / B50	84000 h
Switching Cycles	50000
Power Consumption	4 kWh/1000h
EEI	F