



Abbildung ähnlich

**Product Features**

LC-D/LC-D patch cord, OM4, violet, 5m

- MM-fibre, G50/125 Åm, grade C3 or SM-Faser E9/125Åm, grade C1
- low insertion loss
- latch for connector locking
- pre-polished ceramic ferrule, 1,25 mm
- with kink protection sleeves
- life > 1000 cycles
- 5 m

**Features**

## General

Design	plug, ceramic sleeve
Classification	OM4
Halogen Free	Yes
Country of manufacture	CN
GTIN (EAN)	4043921665015

## Dimensions/Weights without packaging

Cable length mm	5.000
Cable diameter mm	3
Cable construction	50/125µm, Grade C3
Net weight piece kg	0,033

## Certifications

RoHS conform	Yes
--------------	-----

## Logistics Information

Packaging	polybag
Packaging unit Quantity	1
Packaging unit Weight kg	0,039
Packaging unit Width mm	180
Packaging unit Height mm	210
Packaging unit Depth mm	20

## References

Accessories	228030006, 228030012, 228030024, 228030106, 228030112, 228030124, 228030206, 228030212, 228030224, 228030306, 228030312, 228030324, 228030406, 228030412, 228030424
-------------	---

## Similar article

228050005, 228050102, 228050205, 228050305, 228050405, 228050605, 228051005, 228051405