


LED recessed downlight, IP44

**Artikel-Nr. 12109153**



LED recessed downlight, IP44, nickel, round. In a compact design, for installation in tool-less rapid assembly systems. Lamp optimized for installation in furniture and wood-based materials. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Die-cast zinc / Plastic, Degree of protection: according to DIN EN 60529 IP44\*, Protection class: (EN 61140) III, Voltage: 12V, Power: 3.4W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 200lm, Colour temperature: 2.900 K, Light colour : White, Beam angle: 60°, Adjustability: Not adjustable, With control gear: No, Control: Dimming depending on driver.

<b>Artikel-Nr.</b>	<b>12109153</b>
<b>Stand:</b>	26.10.2021 02:13

Colour temperature	2900 K
Colour	Nickel
Beam angle	60 °
Amount of light sources / fittings	1 Qty
Material	Die-cast zinc / Plastic
Power	3,4 W
Lamp	LED
scope of delivery	Including 2,000 mm connecting cable
Colour rendering	CRI > 80

Control	Dimming depending on driver
Outer diameter	65 mm
Built-in diameter	56 mm
Installation depth	14 mm
Voltage	12V
Degree of protection	IP44*
Protection class	III
Adjustability	Not adjustable
Aufbauhöhe	3 mm
Circuit type	Parallel conduction