

Art. no. 732163

High bay lights Highbay Basic, 210/160/110W, DALI,
4000/4500/5700K, black

 **DEKOLOGH**



Special features

- cost-effective and powerful
- particularly energy-efficient and economical
- power adjustable in three stages
- light colour adjustable in three stages
- with Intelli-Data: Dali Parts 251, 252, 253 for luminaire, energy and maintenance data [only item 732163]

Housing Material	Aluminium, Polycarbonate, Steel	Life Time L80 / B10	50000 h
Housing Color	Black	Life Time L80 / B50	60000 h
Protection Class	Protection class I/protective grounding	Switching Cycles	200000
Power Selectable	210 W, 160 W, 110 W	Power Consumption	210 kWh/1000h
Rated Power Consumption Standby	0.5 W	Energy Efficiency Class Lightsource	This product contains a light source of energy efficiency class D.
Rated Input Voltage Frequency	100-277 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Dimmable	Yes		
Control	DALI 2 / DT6 D4i		
Motion Detector	No		
Light Source	Light source changeable TC		
Color Temperature	4000/4500/5700 K		
Colour Consistency	5 SDCM		
Colour consistency light source	5 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	33500/34500/33500 lm		
Rated Angle of Reflection	90 Degree		
UGR	30		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Below		
Height	111 mm		
Diameter	302 mm		
Working Temperature	-10 to 55 °C		
Storage Temperature	-40 to 85 °C		
IP Protection Class	IP 65		
IK Protection Class	IK08		
Life Time L70 / B50	75000 h		