



The ALMAAZ is a classic emergency light with pictogram set to help mark escape routes. As a single-battery light with auto test function, the ALMAAZ, available in flat and tapered designs, performs some of the prescribed DIN functional tests itself and reports faults using an integrated buzzer. Depending on the application, the ALMAAZ can be mounted on the ceiling or on the wall using the rotatable housing. The pictograms supplied indicating escape routes in all directions make the emergency light all the more flexible. Replaceable special pictograms (first aid kit, fire extinguisher) are also optionally available.

#### Special features

- Recognition range 27 m
- Single-battery technology with LiFePO4 battery
- Ceiling or wall mounting possible
- Auto test function with buzzer
- Including pictogram set

<b>Housing Color</b>	White
<b>Protection Class</b>	Protection class II/protective insulation
<b>Rated Input</b>	3 W
<b>Rated Input Voltage</b>	230 V/AC
<b>Frequency</b>	50 / 60 Hz
<b>Power Supply Unit incl.</b>	Yes
<b>Dimmable</b>	No
<b>Motion Detector</b>	No
<b>Accumulator/Battery Operated</b>	Yes
<b>Accumulator/Battery Chemical System</b>	Li-FePO4
<b>Number of Accumulator/Battery</b>	1
<b>Type of Accumulator/Battery</b>	18650
<b>Accumulator/Battery Capacity</b>	1500 mAh
<b>Accumulator/Battery Voltage</b>	3.2 V/DC
<b>Accumulator/Battery Weight</b>	41 g
<b>Light Source</b>	LED, Light source not changeable
<b>Color Temperature</b>	4500 K
<b>Colour Consistency</b>	6 SDCM
<b>Light Exit Surfaces</b>	1
<b>Light characteristics</b>	Direct
<b>Light direction</b>	Below, Side, Rear
<b>Length</b>	283.4 mm
<b>Width</b>	50 mm
<b>Height</b>	186.7 mm
<b>Working Temperature</b>	-5 to 35 °C
<b>IP Protection Class</b>	IP 54