

Han 6B-CP f. HBM/HSM w. cord V2A



Part number	09 30 006 5416
Specification	Han 6B-CP f. HBM/HSM w. cord V2A
HARTING eCatalogue	https://b2b.harting.com/09300065416

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Accessories
Series of hoods/housings	Han [®] B
Type of hood/housing	Protection cover
Description of hood/housing	for bulkhead mounted housings for surface mounted housings Thermoplastic With fixing cord
Туре	Low construction High construction
Version	
Size	6 B

Locking type Single locking lever

Technical characteristics

Limiting temperature	-40 +125 °C
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4 4X 12

Material properties

RoHS	compliant
ELV status	compliant
China RoHS	e

Page 1 / 2 | Creation date 2022-11-04 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Stiftung & Co. KG | Marienwerderstr. 3 | 32339 Espelkamp | Germany

Product data sheet 09 30 006 5416 Han 6B-CP f. HBM/HSM w. cord V2A



Material properties

REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)
Specifications and approvals	
Approvals	DNV GL

Commercial data

Packaging size	1
Net weight	24.2 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140163140
eCl@ss	27440208 Cap for industrial connectors