



The APOLLON narrow, puristic pendant lamp fits into almost any environment seamlessly and in addition to the elegant visual design also delivers a rich warm white light. The APOLLON is available in two different sizes with a matte surface in black and white.

Special features

- Especially narrow design
- High colour rendering
- Suspended mounting up to max. 3,000 mm
- Dimmable

Housing Material	Aluminium
Housing Color	Black
Housing Surface	Matt
Protection Class	Protection class II/protective insulation
Rated Input	42 W
Rated Input Voltage Frequency	200-250 V/AC 50 / 60 Hz
Power Supply Unit incl.	Yes
Connection Type	Clamp
Dimmable	Yes
Control technology	Leading-edge dimmer, Trailing-edge dimmer
Motion Detector	No

Working Temperature	-20 to 40 °C
Storage Temperature	-30 to 60 °C
IP Protection Class	IP 20

Life Time L70 / B50	50000 h
Switching Cycles	25000
Power Consumption	42 kWh/1000h
Energy Efficiency Class	F

Light Source	LED, Light source not changeable
Color Temperature	2700 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	90
Rated Luminous Flux	2475 lm
Rated Angle of Reflection	110 Degree
Light Distribution	Symmetric
Distribution Characteristic 120°	DLS

Light Exit Surfaces	2
Light characteristics	Direct, Indirect
Light direction	Top, Below

Length	1464 mm
Width	80 mm
Height	8 mm
Base length	850 mm
Base width	35 mm
Base height	48 mm
Pendulum Length max.	3000 mm