



Abbildung ähnlich

Product Features

LC-D/SC-D patch cord, OM4, violet, 2m
- MM-fibre, G50/125 Åm, grade C3 or SM-Faser E9/125Åm, grade C1
- low insertion loss
- latch for connector locking at LC
- Push-Pull - connector locking at SC
- pre-polished ceramic ferrule, 1,25 mm(LC) / 2,5mm(SC)
- with kink protection sleeves
- life > 1000 cycles
- 2 m

Features

General	
Design	plug, ceramic sleeve
Classification	OM4
Country of manufacture	CN
GTIN (EAN)	4043921665060
Dimensions/Weights without packaging	
Cable length mm	2.000
Cable diameter mm	3
Cable construction	50/125µm, Grade C3
Net weight piece kg	0,021
Certifications	
RoHS conform	Yes
Logistics Information	
Packaging	polybag
Packaging unit Quantity	1
Packaging unit Weight kg	0,027
Packaging unit Width mm	180
Packaging unit Height mm	210
Packaging unit Depth mm	20
References	
Accessories	228030006, 228030012, 228030024, 228030106, 228030112, 228030124, 228030206, 228030212, 228030224, 228030306, 228030312, 228030324, 228030506, 228030512, 228030524, 228030606, 228030612, 228030624, 228030706, 228030712, 228030724, 228030806, 228030812, 228030824
Similar article	228050102, 228050602, 228050902, 228051005, 228051102, 228051202, 228051402